

GAS GOVERNOR 2"– Pmax 2 bar



Code	Description	Dimension	Pmax
RG050-2B	Gas Governor	2"	2 bar
RGD50-2B	Gas Governor	DN50	2 bar
RG050-FT-2B	Gas Governor with filter	2"	2 bar
RGD50-FT-2B	Gas Governor with filter	DN50	2 bar

If you want test point in and out pls add code TPIO at the end of the code.

TECHNICAL FEATURES


Pmax	inlet max – 2 bar
Setting outlet	10 – 300 mbar – Standard spring supplied 10 – 27 mbar – Other spring on request
Filtering	≤ 50µm – Viledon cartridge
Inlet - Outlet Connection	Thread gas 2" - ISO 228 DN50 - Sliding Aluminium flange PN10
Test point	Inlet / outlet on request – Test point 1/8" NPT
Working Temperature	- 20 °C – + 60 °C
Use	Not aggressive gases of three families – Natural Gas – LPG – Town Gas
Approval	UNI EN 88-2:2008

Materials:


Complete Body	Die – Cast Aluminium Gd – AlSi12Cu - EN AB 46100
Diaphragms	NBR 60Sh – DvGW EN 549
Plastic components	White POM / Pa 66 + 25% Gf

Spring Range:


Color	Range mbar
White	5 - 14 mbar
Yellow	6 - 22 mbar
Neutral	10 - 27 mbar
Red	28 - 70 mbar
Black	60 - 130 mbar
Blue	120 - 300 mbar



FLOW CHART – Gas Governor without filter



FLOW CHART – Gas Governor with filter



DIMENSIONS (mm) and WEIGHT (kgs)

Dimension	A	B	C	D	Weight
2"	301	245	264	235	5,8

